

ROCK HARD T200 Floor Maintenance

LOCATION: Floors protected with T200

FREQUENCY: Daily /Weekly

Needed Equipment & Detergents

175 rpm Floor Machine or a Walk-behind auto scrubber

- Ameripolish SP Clean and Shine Pads

Flat Mop Frame and Microfiber Cleaning Pads

- 17" frame and microfiber pads work best.

6-Gal. Floor Pail and Wringer, Dust Mop & Floor broom

Ameripolish Rejuvenating Cleaner

Daily Maintenance Steps

1. Dustmop and remove debris
2. Add 1 oz. of Ameripolish Rejuvenator per 6-8 gals. of hot water
3. Using the flat mop, dip the mop pad into the cleaning solution and lightly wring the pad out of excess water. Mop over the floor repeating the this several times until complete floor is clean. Allow to dry before traffic.

Weekly Maintenance Steps

1. Elevate chairs and trash receptacles off floor
2. Dustmop and remove debris
3. Using a walk behind Auto Scrubber, fill the freshwater tank with hot water and add 4oz of Ameripolish Rejuvenating Cleaner per 30 gals. of fresh water **OR** 2oz to a 15 gal. fresh water tank **OR** 1oz per 6-8 gal pail. Scrub the entire floor using a walk-behind auto scrubber or a 175 floor machine closely followed by a flat mop to pick up excess water.
4. Using a high speed burnisher or a 175 rpm floor machine with an Ameripolish SP Clean & Shine pad, buff the floor. **DO NOT** rush but rather be slow and steady.
5. Dustmop the floor to remove any dust created before traffic.

NOTE: An auto scrubber is the preferred method over larger areas. Small areas can be maintained with the use of a floor buffer.

