



## DESCRIPTION

**ROCKHARD Matting Agent** is a premium grade, micronized polypropylene, gloss reducing matting agent specifically designed for **ROCKHARD T200 SEALER** (see Loading Rates). **ROCKHARD Matting Agent** provides the optimum, consistent, gloss control desired by today's discerning designers. It is available in Satin and Matte finishes, for 1 gal and 5 gal applications. XPS formula delivers reduced settling of the additive after mixing due to the particulates' spherical shape and size.

## SURFACE PREP

The principles for surface preparation for **ROCKHARD Matting Agent** is directly influenced by the choice or coating it is added to. Refer to [ROCKHARD T200 TDS](#).

## TEMPERATURE/CURE

**ROCKHARD Matting Agent** will not affect the cure rates of sealers or coatings. Refer to [ROCKHARD T200 TDS](#) for temperature and cure rates.

## LOADING RATES

### 1 GAL. APPLICATION

- Base: **ROCKHARD T200 CLEAR-COAT SEALER**
- Additive: Satin (3 oz. / Half Pouch) = Dry Measure Mix with 1 gal. [ROCKHARD T200 SEALER](#)
- Additive: Matte (12 oz. / 1 Full Pouch) = Dry Measure Mix with 1 gal. [ROCKHARD T200 SEALER](#)

### 5 GAL. APPLICATION

- Base: **ROCKHARD T200 CLEAR-COAT SEALER**
- Additive: Satin (15 oz. / 2.5 Pouches) = Dry Measure Mix with 5 gal. [ROCKHARD T200 SEALER](#)
- Additive: Matte (60 oz. / 5 Full Pouches) = Dry Measure Mix with 5 gal. [ROCKHARD T200 SEALER](#)

## MIXING & APPLICATION

- Measure the desired dosage rate as described in the above-mentioned "Loading Rates" section.
- Pour the measured **ROCKHARD Matting Agent** into [ROCKHARD T200 SEALER](#).
- Mechanically mix it into [ROCKHARD T200 SEALER](#) (with jiffy style mixer) for 1 min. at slow speed. (CONTINUALLY SHAKE MIXTURE IN SPRAYER WHILE APPLYING).

## FEATURES

<b>PRODUCT</b>	ROCKHARD Matting Agent
<b>PACKAGING</b>	6 oz. pouch (dry measure) Use in either Satin or Matte applications
<b>MIXING RATIO</b>	See specific instructions below.
<b>USED IN SEALER</b>	ROCKHARD T200 Sealer
<b>SHELF LIFE</b>	18 Months. Under normal conditions: when kept dry and moisture free, out of direct sunlight, shelf life of an unopened container/bag is (18) months from the date of purchase. Storage must be under roof and off floor. Rotate inventory to maintain product that is within limits.

## SUSTAINABILITY SAMPLE

Due to condition of specific sites, always prepare an adequate number of test areas. On-site sample approval is critical on substantial, heavy traffic situation, or custom gloss control and coloration.

## CLEAN-UP

**ROCKHARD Matting Agent** will not affect the clean-up of any sealer or coating.

## DISPOSAL

Contact you local government household hazardous waste coordinator for information on disposal of unused product. Upon curing, left over catalyzed product is not hazardous.

## LIMITATIONS

For use by professionals who have read the complete TDS. **ROCKHARD Matting Agent** follow the limitations of **ROCKHARD T200 SEALER**, see that products appropriate TDS.

## WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufactures/seller's option. XPS Products shall not be liable for cost of labor or direct and/or incidental consequential damage.

## CAUTIONS

**ROCKHARD Matting Agent** will not affect the cure rates of **ROCKHARD T200 SEALER**. Refer to [ROCKHARD T200 SEALER TDS](#) for temperature and cure rates.

