



SAFTY DATA SHEET

XPS POLYTOP 100 A

SECTION1 PRODUCT AND COMPANY IDENTIFICATION

Product name: XPS POLYTOP100 A
Chemical name: Polyaspartic Coating
Company: Xtreme Polishing Systems
Address: 2200 NW 32 St. # 700 Pompano Beach, FL 33069
Email: info@xtremepolishingsystems.com
Fax:
Emergency Phone: US CHEMTEL: 1(800) 255-3924
SDS Date: 2023/2/25

SECTION2 HAZARDS IDENTIFICATION

Hazards Identification:

GHS Classification of the substance or mixture(according to REGULATION (EC)No 1272/2008):

GHS Label elements:



Warning

Skin sensitization,Category1.(H317)

Serious eye damage/Eye irritation,Category 2.(H319)

Hazardous to the aquatic environment,long-term(chronic),Category 3.(H412)

Hazard statements:

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261 Avoid breathing dust /fume /gas/mist /vapours /spray.

P264 Wash...thoroughly after handling.

P272 Contaminated work dothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection /face protection.

P302+P352 IF ON SKIN:Wash with plenty of water / ...





P305+P351+P338 IF IN EYES:Rinse cautiously with water for several minutes.Remove contact lenses ,if present and easy to do.Continue rinsing.

P333+P313 If skin irritation or rash occurs:Get medical advice /attention.

P337+P313 If eye irritation persists :Get medical advice /attention.

P362+P364 Take off contaminated clothing and washit before reuse.

P501 Dispose of contents/container to an approved waste disposal facility.

SECTION3 INFORMATION ON INGREDIENTS

Product name: XPS POLYTOP100 A

Ingredient	Concentration	CAS No.
Polyaspartic resin	100%	136210-30-5

SECTION4 FIRST-AID MEASURES

Skin Exposure:

Immediately remove contaminated clothing and shoes.Wash off with soap and water.Get medical attention if irritation develops and persists.

Eye Exposure:

In case of contact,immediately flush eyes with plenty of water for at least 15 minutes.Get medical attention if irritation develops.The contact lenses must be taken off by professional and trained person.

Inhalation Exposure:

Move the patient out of the contaminated area, lay the patient on his back,and immediately take the patient to the hospital or seek medical attention. If possible, remove prostheses,such as dentures, before starting first aid to prevent blockage of the airway. If breathing stops,give artificial respiration, preferably with a shut- off valve type or bag valve mask type or pocket mask type. Perform CPR if necessary.

Oral Exposure:

If victim is conscious,wash mouth out with water.Get medical aid immediately.

Notes to physician: Basic first aid,decontamination, symptomatic treatment.

SECTION5 FIRE FIGHTING MEASURES

Extinguishing Media:

Carbon dioxide (CO2), Foam, extinguishing powder, in cases of larger fires, water spray should be used.

Special hazards arising from the substance or mixture:

Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen and traces of hydrogen cyanide.

Firefighting:

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes. Use cold water spray to cool fire-exposed containers to minimize risk of rupture. Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Do every possible to avoid the toxic liquid to enter the soil, ground-water or surface waters.





SECTION 6 ACCIDENTAL RELEASE MEASURES

Procedure of Personal Precaution:

Quickly evacuate personnel from the leaked contaminated area to a safe area, isolate them, and strictly restrict access. Personnel wear self-contained positive pressure breathing apparatus and anti-static overalls. Cut off the leakage source. Cover spill vapour with foam. Ensure adequate ventilation/exhaust extraction. Ventilate area to remove vapors or dust. Collect the vapors or dust to containers with EX pump, Spade up and transfer to a dry, clean, lidded container for disposal. Avoid inhalation. Ventilate area and wash spill site after material pickup is complete and disposing them in the specialized site.

Environmental precautions:

Do not allow to escape into waterways, wastewater or soil.

Methods and material for containment and cleaning up:

Take up with absorbent for chemicals or, if necessary with dry sand, earth, vermiculite and diatomite, store in closed containers, and collect for proper disposal.

Measures to secondary hazards:

The spill must be stored in closed containers.

SECTION 7 HANDLING AND STORAGE

Handling:

Ensure adequate ventilation and, if necessary, exhaust ventilation when handling or transferring the product. The personal protective measures described in section 8 must be observed. Avoid contact with skin and eyes absolutely. Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at end of work and use skin-protecting ointment. Keep working clothes separately. Change contaminated or soaked clothing immediately.

Storage:

Keep container dry and tightly closed in a cool and well ventilated place. Avoid contact with fire/heat. Material can be stored safely at ambient temperatures under 40°C. Stored in closed containers. Keep away with oxidant, acid, alkali, deoxidizer, hyperoxide. Smoking is forbidden. Take care of the opened containers to avoid leaking.

SECTION 8 EXPOSURE CONTROL/PPE

Occupational exposure limits:

Country specific exposure limits have not been established or are not applicable.

Industrial Hygiene / Ventilation Measures:

Good industrial hygiene practice dictates that worker protection should be achieved through engineering controls, such as ventilation, whenever feasible. When such controls are not feasible to achieve full protection, the use of respirators and other personal protective equipment is mandated. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Curing ovens must be ventilated to prevent emissions into the workplace.





Exposure controls Respiratory protection:

Respiratory protection measures are required in the work area with insufficient ventilation and when spraying products. Appropriate certified respirators, such as activated carbon and dust respirator (such as filter unit combination A2-P2) must be used. If the respiratory tract and skin are susceptible to allergy (such as asthma, chronic bronchitis and chronic skin diseases), it is recommended not to operate this product. Symptoms of respiratory tract infection may occur several hours after overexposure.

Hand Protection:

Gloves should be worn such as nitrile rubber gloves, butyl rubber gloves and neoprene gloves.

Eye Protection:

When directly handling liquid product, eye protection is required. Examples of eye protection include a chemical safety goggle or chemical safety goggle in combination with a full face shield when there is a greater risk of splash.

Skin and body protection:

Avoid all skin contact. Depending on the conditions of use, cover as much of the exposed skin area as possible with appropriate clothing to prevent skin contact, such as gloves, long sleeved shirts and pants.

Additional Protective Measures:

Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of this product. Follow all label instructions.

SECTION 9 PHYSICAL/CHEMICAL PROPERTIES

Physical appearance(20°C)	Liquid
Odor	Odorless
Odor threshold	No data available
PH	No data available
Melting point/freezing point	No data available
Boiling point/range	No data available
Flash Point	Ca.95°C
Freezing point:	No data available
Explosion Limits	No data available
Steam density	No data available
Vapour Pressure	No data available
Vapour Density	No data available
Relative density(water=1)	1.08±0.02 g/cm ³ at 25 °C
Solubility	No data available
N-octanol /water partition coefficient	No data available
Auto-ignition temperature	No data available





Ignition temperature	No data available
Decomposition temperature	No data available
Viscosity, dynamic	Ca.400 mPa.s at 25 °C

Section10 CHEMICAL STABILITY AND REACTIVITY INFORMATION

Stability:

Stable under normal temperatures and pressures.

Conditions to avoid:

Avoid extreme heat,static,percussion,sunshine.

Hazardous Polymerization:Hazardous polymerization does not occur.

Materials to avoid:

Oxidant, acid, alkali, deoxidizer, hyperoxide, acid chloride, isocyanate.

Possibility of hazardous reactions:

Stable under normal temperatures and pressures.

Materials to Avoid:

Strong oxidizing agents.

Hazardous Polymerization:

Will not occur.

Hazardous Decomposition Products:

No risk of aggregation..

Hazardous Decomposition Products:

Nitrogen oxides,carbon oxides,amines,etc.

SECTION11 TOXICOLOGICAL INFORMATION

11.1 Acute toxicity:

Information on toxicological effects Acute toxicity,oral

※Polyaspartic resin

LD50 rats:>2000 mg/kg

Method:Directive 67/548/EEC,Annex V,B.1

Toxicological studies on similar products

Acute toxicity,inhalation

※Polyaspartic resin

LC50 rats,male/female:>4.224 mg/l,4 h

Test environment:Dust/Smoke

Method:OECD Test Guideline 403

Toxicological studies on similar products

Evaluation:This substance or mixture has no acute inhalation toxicity

Acute toxicity,dermal





※Polyaspartic resin
LD50 rat:>2000 mg/kg
Toxicological studies on similar products

11.2 Primary skin irritation

※Polyaspartic resin
Species:rabbit
Result:Slight irritant
Classification:No skin irritation
Method:OECD Test Guideline 404
Toxicological studies on similar products

11.3 Primary mucosae irritation

※Polyaspartic resin
Species: rabbit
Result: slight irritant
Classification: No eye irritation
Method: OECD Test Guideline 405
Toxicological studies on similar products

11.4 Sensitisation

※Polyaspartic resin
Skin sensitisation according to
Magnusson/Kligmann (maximizing test):
Species: Guinea pig
Result: positive
Classification: May cause sensitization by skin contact (Sub cat. 1B)
Method: OECD Test Guideline 406
Toxicological studies on similar products
Respiratory sensitization
Toxicological studies on the product are not yet available.

11.5 Germ cell mutagenicity

※Polyaspartic resin
Test Species: Salmonella/microsome assay (Ames test)
Result: No indication of mutagenicity.
Method: OECD Test Guideline 471
Toxicological Studies on Similar Products Test
Type: In vitro Chromosomal Aberration
Result: Negative
Method: OECD Test Guideline 473
Toxicological Studies on Similar Products

11.6 Carcinogenicity





※Polyaspartic resin

Toxicological studies on the product are not yet available.

11.7 Reproductive toxicity

Reproductive toxicity/fertility

※Polyaspartic resin

NOAEL (parents, generally toxicity): 200 mg/kg NOAEL (parents, fertility): 1.000 mg/kg

NOAEL (offspring): 1.000 mg/kg

Test type: Two-generation study

Species: rat, male/female

Application Route: Oral

Dose Levels: 0 - 40 - 200 - 1000 mg/kg

Method: OECD Test Guideline 416

Toxicological studies on similar products

Reproductive toxicity/teratogenicity

※Polyaspartic resin

NOAEL (teratogenicity):1.000 mg/kg

NOAEL(maternal):1.000 mg/kg

NOAEL(developmental toxicity):1.000 mg/kg Species:Rat,female

Application Route:Oral

Dose Levels:0-100 -300 -1000 mg/kg

Method:OECD Test Guideline 414

Toxicological studies on similar products

11.8 Specific target organ toxicity-single exposure

※Polyaspartic resin

Based on available data,the classification criteria are not met.

11.9 Specific target organ toxicity-repeated exposure

※ Polyaspartic resin

Based on available data,the classification criteria are not met.

SECTION12 ECOLOGICAL INFORMATION

12.1 Toxicity Acute

Acute Fish toxicity

※Polyaspartic resin

LC5066 mg/l

Species:Danio rerio (zebra fish)

Exposure duration:96 h

Method:OECD Test Guideline 203

Ecotoxicological studies of similar products

Acute toxicity for daphnia





※Polyaspartic resin
LC5066 mg/l
Species:Danio rerio (zebra fish)
Exposure duration:96 h
Method:OECD Test Guideline 203
Ecotoxicological studies of similar products

Acute toxicity for algae

※Polyaspartic resin
ErC50 >100 mg/l
Species: scenedesmus subspicatus
Exposure duration: 72 h
Method: Directive 67/548/EEC, Annex V, C.3. Ecotoxicological studies of similar products

Acute bacterial toxicity

※Polyaspartic resin
EC50 >1,000 mg/l
Species: activated sludge
Exposure duration: 3 h
Method: OECD Guidelines for the Testing of Chemicals 209
Ecotoxicological studies of similar products

12.2 Persistence and degradation

Biodegradability

※Polyaspartic resin
LC5066 mg/l
Species:Danio rerio (zebra fish)
Exposure duration:96 h
Method:OECD Test Guideline 203
Ecotoxicological studies of similar products

Stability in the water

※Polyaspartic resin
Half life: 655 h at 25 °C (pH: 4)
Method: OECD Test Guideline 111
Studies on similar products
Half life: 25.4 h at 25 °C (pH: 7)
Method: OECD Test Guideline 111
Studies on similar products
Half life: 16.8 h at 25 °C (pH: 9)
Method: OECD Test Guideline 111
Studies on similar products

12.3 Bioaccumulative potential





※Polyaspartic resin
 Bioconcentration factor (BCF): value calculated 1.872
 The substance hydrolyzes rapidly in water.
 An accumulation in aquatic organisms is not to be expected.

12.4 Mobility in soil

※Polyaspartic resin
 Adsorption/Soil
 og Koc value:4.2 -5.1
 Method:EU Method C.19
 Studies on similar products Not available

Section 13 DISPOSAL CONSIDERATIONS

Waste disposal method:

Products are not allowed to be discharged into sewers and water sources.

Empty Container Precautions:

Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapours and gases are formed. Do not reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed prior to disposal.

Waste Disposal Method:

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

SECTION 14 TRANSPORT INFORMATION

Item	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN-Number	NO	NO	NO
UN Proper shipping name	NO	NO	NO
Transport hazard Class	NO	NO	NO
Packaging group	NO	NO	NO
Environmental hazards	NO	NO	NO
Special precautions for user Transport in bulk according	See section 2	See section 2	See section 2
to Annex II of Marpol and the IBC Code	Not available	Not available	Not available





SECTION 15 REGULATORY INFORMATION

The following laws, regulations and standards make corresponding provisions on the safe use, storage, transportation, handling, classification and marking of chemicals.

Law of the People's Republic of China on the Prevention and Control of Occupational Diseases:
Classification and Catalogue of Occupational Diseases: Not listed.

Hazardous Chemical Safety Management Regulations:

Catalogue of hazardous chemicals: Not listed.

Inventory of explosive hazardous chemicals: not listed.

List of hazardous chemicals under key supervision: not listed.

GB18218-2009 " Identification of Major Hazardous Sources of Hazardous Chemicals": Not listed.

Labor Protection Regulations for Workplaces Using Toxic Substances:

List of Highly Toxic Substances: Not listed.

Regulations on the Administration of Precursor Chemicals:

Classification and variety of precursor chemicals: not listed..

SECTION 16 OTHER INFORMATION

Other Information:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

